...smoothness of...

Inspection Excavation...

...the depth indicated on...

...conditions for soil bear...

...matter is to be brought im...

...building.

Protect Walls:- Protect all walls and other construction so theywill not be damaged, dirtied or smeared with roofing material.

Guarantee:- The roofing contractor is to furnish a guarantee covering his maintaining and keeping the roof, parapet walls and other work under heading "Roofing" in a watertight condition and free from leaks for a period of ten years, and should the roof leak or deteriorate, due to inferior work or materials, the roofing contractor shall stop all leaks, and water entering the building, and repair or replace such portions or construction, as may be directed without any expense to the owner or the general contractor.

...and installing of all hardware required for the complete building, except for the steel sash and ...

...logue of the following manufacturers, unless stated to the contrary:

Stanley Works
Yale & Towne Mfg. Co.
H. B. Ives Company
Chicago Spring Butt Company

Keys:- All locks for inside doors to be different; two keys each lock and two master keys for all locks; master keys to be same as master keys at plant now.

Doors A and B Double Outside 10' x 13'

Butts BBZ-280 5 x 5, 4 butts each door, no finish.
Panic Bolt Vonnegut 9127 R.

C and D Outside Sliding Doors (C only Metal Covered)

No. 3 Track Brackets 24" Centers to Center
2 #6 Adjustable Hangers per door,
Guide Center RH-#171
2-BW 272 End Door Stops
2-Flush Pulls #15